

度数	S (-)	TC (-)															
		0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00
0.00																	
0.25																	
0.50																	
0.75																	
1.00																	
1.25																	
1.50																	
1.75																	
2.00																	
2.25																	
2.50																	
2.75																	
3.00																	
3.25																	
3.50																	
3.75																	
4.00																	
4.25																	
4.50																	
4.75																	
5.00																	
5.25																	
5.50																	
5.75																	
6.00																	
6.25																	
6.50																	
6.75																	
7.00																	
7.25																	
7.50																	
7.75																	
8.00																	
8.25																	
8.50																	
8.75																	
9.00																	
9.25																	
9.50																	
9.75																	
10.00																	

度数	S (+)	TC (+)															
		0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00
0.00	×																
0.25																	
0.50																	
0.75																	
1.00																	
1.25																	
1.50																	
1.75																	
2.00																	
2.25																	
2.50																	
2.75																	
3.00																	
3.25																	
3.50																	
3.75																	
4.00																	
4.25																	
4.50																	
4.75																	
5.00																	
5.25																	
5.50																	
5.75																	
6.00																	
6.25																	
6.50																	
6.75																	
7.00																	
7.25																	
7.50																	
7.75																	
8.00																	

混合乱視

度数	S (+)	TC (-)															
		0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00				
0.25																	
0.50																	
0.75																	
1.00																	
1.25																	
1.50																	
1.75																	
2.00																	
2.25																	
2.50																	
2.75																	
3.00																	

1、色塗り範囲は、工場在庫範囲

2、他範囲は、特注研磨品範囲



レンズ梱包仕様



仕様	
設計	非球面設計
屈折率	1.67
比重	1.35
アッペ数	32
紫外線カット	UV400
コート	超撥水コート

カラー加工	
○ アリアーテトレスカラー	
○ M-POSオリジナルカラー	
○ 見本染色 不可	

研磨加工	
偏心	不可
プリズム	3△まで可
外径指定	1mm単位/ 最小55mm
厚み指定	可